

NISCA's NEW
PR-C201
Retransfer
Plastic Card Printer



Features

- 600 dpi
- 24 bit color
- Printing speed 145 cards/hr

Product Specifications

PR-C201

Print	Print Method	Dye-sublimation retransfer printing
	Resolution	600DPI
	Input	R/G/B 256 level
	Output	Y/M/C/UV 256 level
	Printing area	Over the edge
Speed	Printing speed (Single printing: YMCK)	More than 25.0s full color YMCK (145 cards/hr)
	Printing speed (Double printing: YMCKK)	More than 40.0s full color YMCKK (90 cards/hr)
Capacity	Feeder capacity	250 cards (if card thickness is 0.76mm)
	Card exit capacity	250 cards (if card thickness is 0.76mm)
Card	Card thickness	0.25 to 1.0 mm
	Card size	ISO7810
	Card material	PVC, PET, PC, ABS (Except PVC cards need prior confirmation)
Display	Display	LCD Panel (with back light), LED, Operation button
Size	Dimensions	17.13(H) x 13.39(W) x 12.60(D) Inches (435(H) x 340(W) x 320(D)mm)
	Weight	Less than 44 lbs. (20kg)
Power	Power Source	90 - 125VAC 220 - 240VAC 50/60Hz
	Power consumption	Less than 3A (100V)
Temperature	Operating temperature	15 to 35°C - 20 to 80% humidity
Drivers	I/F	USB and Ethernet 10 Base-T, 100 Base-T
	Drivers	XP, Vista, Win 7, Win 8 (32 & 64 bits)
Ribbon	Ribbon capacity	500 images / roll (YMCK ribbon)
	Film Ribbon	Clear Retransfer, Holographic Retransfer
	Ink Ribbon	YMCK, YMCKK, YMCKH (for except PVC Card) YMCKI (for smart card), YMCFK (UV ink)
Agency Listing	Agency listing	UL/CSA/CE/FCC/CCC
Life	MTBF	100,000 prints
	Print head life	Limited lifetime print head warranty**
Other	Extendibility	2 USB HUBS (inside printer)
	Memory size	64MB
Options	Laminator	NiSCA dedicated retransfer laminator
	Encoder	Mag Encoder, Contact Encoder, Contactless Encoder

*Specifications subject to change without notice

** Contact Team NiSCA for details..



www.teamnisca.com
 info-asia@eamnisca.com
 South East Asia: 662-632-8077
 Other Asia Area: 81-3-5440-8340
 Outside Asia: 1-732-271-7367

